



SAFETY DATA SHEET

MORTECH OIL 220

Prepared according to Annex II of EC regulation 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME MORTECH OIL 220

SUPPLIER OMV PETROL OFİSİ A.Ş.
Ayazağa Eski Büyükdere Cad.
No:33-37 B Blok 34398
Maslak-Istanbul/TURKEY
Tel: +90 212 329 1500
Fax: +90 212 329 1896
www.poas.com.tr
info@poas.com.tr

PRODUCT NO. 21220

APPLICATION Industrial oil

2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
Alkyl phenol			< 1%	N;R50/53.
Alkyl phosphate			< 1%	C;R34.
Long chain alkenyl amine			< 1%	Xn;R22. C;R35. N;R50.
Long chain alkyl amine			< 1%	T;R23/24. Xn;R22,R48/20. C;R34. N;R50/53. R43.
Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)	278-012-2	74869-22-0	60-100%	-
NAPHTHALENE	202-049-5	91-20-3	< 1%	Carc. Cat. 3;R40 Xn;R22 N;R50/53
Petroleum distillates			< 1%	Xn;R65. R66.
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.; KEROSENE - UNSPECIFIED	265-198-5	64742-94-5	< 1%	Xn;R65

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

Get medical attention if any discomfort continues.

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Get medical attention if any discomfort continues.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

MORTECH OIL 220

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

SPILL CLEAN UP METHODS

Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water sources or sewer.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
NAPHTHALENE	WEL	10 ppm	53 mg/m ³	15 ppm	80 mg/m ³	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of inhalation of vapours.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Yellow		
ODOUR	Characteristic.		
RELATIVE DENSITY	0.89 g/ml 15	VISCOSITY	198-242 cSt 40

MORTECH OIL 220

FLASH POINT (°C) 260 OC (Open cup).

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid excessive heat for prolonged periods of time.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION

INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing.

INGESTION

May cause discomfort if swallowed.

SKIN CONTACT

Liquid may irritate skin.

EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

ROAD TRANSPORT NOTES

Not Classified

RAIL TRANSPORT NOTES

Not classified.

SEA TRANSPORT NOTES

Not classified.

AIR TRANSPORT NOTES

Not classified.

TUNNEL RESTRICTION

(D/E)

CODE

15 REGULATORY INFORMATION

RISK PHRASES

NC Not classified.

SAFETY PHRASES

NC Not classified.

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

16 OTHER INFORMATION

REVISION COMMENTS

Company name changed

MORTECH OIL 220

ISSUED BY

Certificated from the Turkish Standards Institute (TSE) to prepare Safety Data Sheet (Certificate no: SDS - 0397)

REVISION DATE 16.06.2011

DATE 15.02.2011

RISK PHRASES IN FULL

R34	Causes burns.
R35	Causes severe burns.
R22	Harmful if swallowed.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
NC	Not classified.
R66	Repeated exposure may cause skin dryness or cracking.
R23/24	Toxic by inhalation and in contact with skin.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R50	Very toxic to aquatic organisms.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.